



HARDWARE PLATFORM

# CP4S

4 Channel HD  
Vehicle Recorder



## VISIBILITY + PROTECTION

The CP4S is an HD, cloud-connected mini-DVR designed to record high-resolution telematics data providing powerful insights into driving dynamics like harsh braking, cornering and accelerating. Supporting up to 4 cameras, video can be captured in and around vehicles with an optional monitor to increase driver visibility of blindspots. Events, including accidents, captures the 10 seconds prior to the event, the event and 10 seconds post and automatically uploads to the cloud. Packed with sensors and high-speed connectivity, the CP4S provides real-time decision making capabilities for operators and managers to coach drivers, capture incidents and reduce cost.

## HIGHLIGHTS

### Gain Control

Take telematics to the next level with video that transforms ordinary data into insight.

### Mitigate Risk

Eliminate the unexpected with a solution to improve driver performance and get ahead of dangerous behavior.

### Protect Your Future

Invest in solutions that will fit your needs today and expand with your growing business.

+

- 720p HD video across all 4 channels
- Multiple camera options with plug-and play compatibility
- Supports up to 256GB storage capacity
- 4G/LTE data transmission for instant notification of events
- Compact and secure design

# CP4S Technical Specifications



<b>Size / Weight</b>	120 mm x 28mm x 90 mm / 166 g
<b>LED</b>	Green LED (network), Blue LED (recording), Red LED (error)
<b>RTC</b>	Internal Battery
<b>Operational Temperature</b>	-10° C ~ 55° C
<b>Super Capacitor</b>	Enables Recording of Last File & Safe Shutdown
<b>Power Consumption</b>	Max. 36 W
<b>Recording Resolution</b>	Up to 4 Channels HD
<b>Recording Speed</b>	4 Channels HD at 15 FPS
<b>Recording Mode</b>	Continuous, Event and Dual Mode
<b>AV In/Out</b>	1 x Audio In (internal/external microphone) / 1 x Video Out; 1 x Audio Out
<b>Storage</b>	Supports SD Cards Up to 256 GB
<b>Cellular</b>	CP4S-NA: [CAT4] B2/B4/B5/B12/B13/B14/B66/B71; [3G] B2/B4/B5 CP4S-EU: [CAT4] B1/B3/B7/B8/B20/B28A/B38/B40/B41; [3G] B1/B8
<b>Delayed Power Shutdown</b>	Yes
<b>GPS / GLONASS</b>	External GPS / GLONASS
<b>G-Sensor</b>	Internal 3-Axis G-Sensor
<b>Gyro</b>	3 Axis (X,Y,Z), Output Rate: 100 Hz
<b>Alarm In / Out</b>	4 x Alarm In / 1 x Alarm Out
<b>Max Data Rate</b>	Download: 100 Mbps; Upload: 50 Mbps
<b>WiFi</b>	Built In with CP4S-W Model
<b>Power Input</b>	DC 12V/24V, 3A
<b>SmartAPI Integrated</b>	Yes
<b>Data Analysis Software</b>	Windows Only
<b>Viewer Software</b>	Windows and MacOS
<b>Warranty</b>	2-year Standard