



ADD-ON CAMERA

SVA035-A

Side/Rear Camera



HIGHLIGHTS

Commercial Grade

Ruggedized engineering to support the harsh environments of any fleet application.

High Quality

Built with premium components to ensure excellent picture quality in any conditions.

Performance Backed

All add-on cameras come with a 2-year warranty against any manufacturer's defect.

+

- 1/3" Next Chip NEPIS CCD, Sony
- Wide View 145°, (2.45mm)Lens
- 650 TV lines
- Wide Dynamic Range (WDR)
- Digital Noise Reduction (DNR)
- DC 5~12V 12
- Infrared LEDs for Night-time Recording
- Easy Windshield Installation with 3M Adhesive
- Simple and Secure Angle Control

SVA035-A Technical Specifications



Synchronization	Internal	TV Mode	NTSC / PAL
White Balance	2000 ~ 8000K Automatic Tracking		
D-WDR	Off / Low / Middle / High		
Power Supply	DC12V, 150mA (LED ON)/ 80mA (LED OFF) (DC 7V - DC 43V)		
Day and Night	True Day / Night	Night View Distance	8M
Storage Temperature	-30°C ~ +80°C	Operating Temperature	-20°C-+60°C (Humidity: 10%-85% RH)
Dimensions	60.8mm(W) x 69.6mm(D) x 71.6mm(H)		
Language	English		
Housing Color	Black	Mirror	ON/ OFF (Option)
Image Device	1.3 Mega-Pixel Sony CMOS Sensor		
Image Processor	NVP 2431		
AGC	Off / Low / Middle / High		
Effective Pixels	1305(H)x 1049M= 1.37M		
Video Output	AHO: 1.0 (720P)/ CVBS: 1Vp-p ±10%, 75 Ω		
Scanning Mode	Progressive		
BLC	Off / Low / Middle / High		
Scan Frequency	(V)59.94 Hz, (H)15.734 KHz (NTSC)(V)50 Hz, (H) 15.625 KHz (PAL)		
Infrared LED	12 IR LEDs		
Lens	2.5mm lens(145°) [3 MEGA LENS]		
Sensitivity	0.1Lux (F1.2,@50IRE)		
S/N Ratio	More than 50dB AGC OFF		
Compatible Hardware Platforms	CP4S, CRXS		
Required Accessories	CP4S: SVA-05-EXT-B CRXS: SVA-05-EXT-A		
Warranty	2-year standard		